

New Acland Coal Pty Ltd (NAC) undertakes air quality monitoring as part of the environmental monitoring program for the Jondaryan Rail Loading Facility (JRLF). The following air quality data is provided to the Jondaryan community.

Table 1: Dust deposition and compositional monitoring results for April 2022

Site	Dust Deposition (mg/m ² /day)	EA Criteria (mg/m ² /day)	Compositional Analysis ¹			Comments
			Major (>20%)	Minor (5% - 20%)	Trace (<5%)	
JD1	20	120	Insects (50%)	Mineral Material (20%) Vegetation (10%) Polysaccharide Slime (10%) Coal (10%)	-	JRLF to east. Dirt & gravel immediately surrounding. Gravel driveways to west, north-west, north & north-east. Road to south-west, west & north-west. Gravel edge road to north-west, north & north-east. Highway & rail to north-west, north & north-east. Bare paddock to north-east, east & southeast. Gravel road to east & south-east.
JD2	23	120	Insects (70%)	Copper Sludge (10%) Coal (10%) Polysaccharide Slime (5%) Mineral Material (5%)	Vegetation (<5%)	JRLF to east-south-east. Grass immediately surrounding. Highway & rail to north-west, north & north-east. Gravel edge road to north-east, east, south-east & south. Gravel road to southeast, south & south-west.
JD3	40	120	Insects (30%) Polysaccharide Slime (30%)	Vegetation (10%) Mineral Material (10%) Copper Sludge (10%) Coal (10%)	-	JRLF to east-south-east. Grass & garden immediately surrounding. Highway & rail to north-west, north & north-east. Gravel driveways to north, north-east, east, south-east & south. Road to north, north-east & east. Gravel edge road to south-east, south & south-west.
JD4	23	120	Insects (65%)	Polysaccharide Slime (15%) Mineral Material (10%) Coal (10%)	Vegetation (<5%)	JRLF to south-east. Grass immediately surrounding. Cropped paddock to north. Local roads in all directions. Highway & rail to south-east, south & southwest.
JD5	27	120	Insects (50%)	Mineral Material (15%) Coal (15%) Polysaccharide Slime (10%) Vegetation (10%)	-	JRLF to east-south-east. Grass immediately surrounding. Highway & rail to north-west, north, north-east, east & south-east. Road to north-west, north, north-east, east & south-east. Bare ground to the north.

¹ A semi-qualitative visual analysis of a representative portion of the collected sample which is as consistent as possible (however potentially biased) to that of the complete sample

When measured at a sensitive place, the allowable maximum level of the release of dust from JRLF is 120 milligrams per square metre per day (120 mg/m²/day as stated in JRLF's Environmental Authority (EA)). The predominant wind directions for April 2022 were East (32.8%), South East (22.8%) and South (14.0%). The predominant wind speeds were light breeze to gentle breeze ².

²Wind speed classification uses the Beaufort scale

TSP 24 Hour Average April 2022





Figure 1: Jondaryan Township TSP continuous monitoring 24 Hr average results for January 2022

Comments: Ecotech Pty Ltd has been contracted by NAC for the maintenance and data collection at a TEOM site located in the Jondaryan Township which continuously measures Total Suspended Particulate (TSP) matter. When measured at a sensitive place, the maximum level of the release of TSP from the JRLF (24 hour rolling average) is 80 micrograms per cubic metre (80 µg/m³) as stated in the JRLF's EA. Any exceedances of this limit are displayed in Figure 1 (above). The TEOM does not distinguish between particulate matter sources. The predominant wind directions for April 2022 were East (32.8%), South East (22.8%) and South (14.0%). The predominant wind speeds were light breeze to gentle breeze. Unit availability for TSP determination was 99.5% of the sample period. If there are any queries regarding the air quality monitoring undertaken for the Jondaryan Rail Loading Facility, please contact Andrew Scouller at the New Acland Coal Mine during business hours on (07) 4694 8834.

Issued by:
 Andrew Scouller
 CHPP Manager
 New Acland Coal Pty Ltd


 Date: 02/06/22